



Self-Adhesive Fiberglass Mesh Drywall Joint Tape

Technical Information Data Sheet

<u>Property</u>		<u>Metric</u>	<u>Imperial</u>	<u>ASTM Method</u>
Construction: (per 10cm per inch)	Warp	36	9	D-3775
	Weft	36	9	
Weight: (g/m ² - oz/yd ²)		62.7 +/- 2.7	1.85 +/- 0.1	D-3776
DPU (Coating and PSA on fabric in weight %)		40-45%	40-45%	SGTF
Thickness: (per mm - per inch)		0.3	0.01	D-1777 & C-475
Tensile Strength: (N/2.54cm - lbs/in)	Warp	222	50	C-474
	Weft	467	105	

Weave Type: Non Interlaced Fiberglass Technology (NIFt)

All statements herein are expressions of opinion, which we believe to be accurate and reliable, but are presented without guarantee or responsibility on our part. Statements concerning possible use of our product are not intended as recommendations for their use in the infringement of any patent. No patent warranty of any kind express or implied is made or intended.

Values presented above are nominal and only to be used as guidelines.

Saint-Gobain Technical Fabrics
345 Third Street, Suite 615 Niagara Falls, NY 14303 Inside Sales: 1 (800) 762-6694 Fax: (716) 285-5515