



**T.R. Industries**  
**The Surface Care Experts**

### TR-216 HI-TEMP LIQUID RELEASE

- DESCRIPTION:** A blend of synthetic and natural High Temperature waxes in petroleum distillates which provides a uniform non-settling mix.
- PRODUCT FEATURES:**
- \* Fast and easy application that dries rapidly for improved production cycles.
  - \* Polishes to a high gloss without streaking.
  - \* Reduces excessive wax build-up.
- USES:** Recommended as a liquid production release in all fiberglass and cultured marble fabrication. As with most liquid releases, it is not recommended for break-in on new or reconditioned molds. Suggest using the TR-108, 102, or 104 paste wax in conjunction with TR-301 Sealer Glaze for conditioning new tools and prototype masters. (Please refer to our catalog for additional product information and mold prep procedure).
- APPLICATION:** Apply either by wipe or spray method. When spraying a fine mist should be used without excess flooding. For wiping saturate a soft cloth and apply uniform even coat. Allow to dry a few minutes to a slight haze, then polish to a gloss finish with desired soft towelling.  
Shake or stir well before use and observe necessary safety precautions especially when spraying.

**\* Gel-Gloss \* Seapower \* Mold Release Agents**

11022 Vulcan Street • South Gate, CA 90280 • 562.923.0838 phone • 562.861.3475 fax • [www.trindustries.com](http://www.trindustries.com)